



LG
Life's Good
(R22)




SINGLE SPLIT STANDARD

WALL MOUNTED TYPE (Cooling & Heating)

This can be easily installed in a small space and has exceptional cooling capacity. Designed for low-noise operation, it ensures a pleasant air conditioned environment. It also has Jet Cool for high level cooling and clean air supply through a Standard air purifying system.





SINGLE SPLIT STANDARD

HS-C0964GA0 / HS-C1264GA0 / HS-C1864GA0 / HS-C2665GA0
 HS-H0964GA0 / HS-H1264GA0 / HS-H1864GA0 / HS-H2665GA0

Indoor & Outdoor

FEATURES

- Gold Fin Anti Corrosion™ ●Jet Cool™ ●Natural Wind by CHAOS Swing
- Auto Restart ●Wireless Remote Controller ●Quiet Operation ●Sleep Mode
- Auto Operation ●7 hour OFF Setting Timer ●One-Touch Air Filter (Anti-Bacteria) ●Healthy Dehumidification.



Note: Due to our policy of innovation some specifications may be changed without notification. The exact appearance of products may vary from the images shown.

(R22)

INDOOR UNIT



| | | HS-C0964GA0 | HS-C1264GA0 | HS-C1865GA0 | HS-C2665GA0 | HS-H0964GA0 | HS-H1264GA0 | HS-H1865GA0 | HS-H2665GA0 |
|--------------------------|-----------|------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Nominal Capacity (Rated) | Cooling | Btu/hr 9,000 | 12,000 | 18,500 | 26,000 | 9,000 | 12,000 | 18,500 | 26,000 |
| | | Kw 2,635 | 3,516 | 5,400 | 7,618 | 2,635 | 3,516 | 5,400 | 7,618 |
| Heating | Btu/hr | - | - | - | - | 9,900 | 13,200 | 19,800 | 27,000 |
| | Kw | - | - | - | - | 2,900 | 3,867 | 5,801 | 7,911 |
| Running Current | Cooling | A 4.2 | 6.0 | 9.2 | 12.6 | 4.2 | 6.0 | 9.2 | 12.6 |
| | Heating | A 4.0 | 4.8 | 8.4 | 12.6 | 4.0 | 4.8 | 8.4 | 12.6 |
| Power Supply | | Ø / V /Hz 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 |
| Operational Temp. Range | Cooling | °C 18 - 30 | 18 - 30 | 18 - 30 | 18 - 30 | 18 | 18 | 18 | 18 |
| | Heating | °C - | - | - | - | 30 | 30 | 30 | 30 |
| Air Circulation | | CMM /CFM 6.8 (240) | 8.8 (311) | 12.5 (442) | 14.0 (495) | 6.8 (240) | 8.8 (311) | 12.5 (442) | 14.0 (495) |
| Sound Level (H / M / L) | | dB(A) ±3 32 / 29 / 24 | 37 / 33 / 30 | 40 / 37 / 30 | 46 / 43 / 39 | 32 / 29 / 24 | 37 / 33 / 30 | 40 / 37 / 30 | 46 / 43 / 39 |
| Dehumidification Rate | | l/h 1.2 (2.56) | 1.5 (3.20) | 1.8 (3.83) | 2.8 (5.95) | 1.2 (2.56) | 1.5 (3.20) | 1.8 (3.83) | 2.8 (5.95) |
| Dimensions (W x H x D) | Body | mm 840 x 270 x 153 | 840 x 270 x 153 | 1090 x 300 x 180 | 1090 x 300 x 180 | 840 x 270 x 153 | 840 x 270 x 153 | 1090 x 300 x 180 | 1090 x 300 x 180 |
| | Ind.Panel | mm 33.1 x 10.6 x 6.1 | 33.1 x 10.6 x 6.1 | 42.9 x 11.8 x 7.1 | 42.9 x 11.8 x 7.1 | 33.1 x 10.6 x 6.1 | 33.1 x 10.6 x 6.1 | 42.9 x 11.8 x 7.1 | 42.9 x 11.8 x 7.1 |
| Weight | Body | kg 7 | 7 | 13.5 | 13.5 | 7 | 7 | 13.5 | 13.5 |
| Drain Hose | | mm 12.2 | 12.2 | 12.2 | 12.2 | 12.2 | 12.2 | 12.2 | 12.2 |
| Piping Connections | Liquid | mm(inch) 6.35 (1/4) | 6.35 (1/4) | 6.35 (1/4) | 6.35 (1/4) | 6.35 (1/4) | 6.35 (1/4) | 6.35 (1/4) | 6.35 (1/4) |
| | Gas | mm(inch) 9.52 (3/8) | 12.7 (1/2) | 12.7 (1/2) | 15.88 (5/8) | 9.52 (3/8) | 12.7 (1/2) | 12.7 (1/2) | 15.88 (5/8) |

OUTDOOR UNIT

| | | HS-C0964GA0/HS-H0964GA0 | HS-C1264GA0/HS-H1264GA0 | HS-C1865GA0/HS-H1865GA0 | HS-C2665GA0/HS-H2665GA0 |
|--------------------|--------------------|------------------------------|-------------------------|-------------------------|-------------------------|
| Compressor | Capacity | Btu/hr 9,000 | 12,000 | 18,500 | 26,000 |
| | Type | Rotary | Rotary | Rotary | Rotary |
| Refrigerant Charge | Charge | g 800 | 830 | 1170 | 1400 |
| | Type | R22 | R22 | R22 | R22 |
| Fan Motor | Input / Output | W 63.2 / 25 | 63.2 / 25 | 145 / 74 | 145 / 74 |
| | Type | AC Induction | AC Induction | AC Induction | AC Induction |
| Noise Level | Sound Press (1m) | dB(A) ±3 47 | 49 | 56 | 56 |
| Dimensions | (W x H x D) | mm 770 x 245 x 540 | 770 x 245 x 540 | 870 x 655 x 320 | 870 x 655 x 320 |
| Net Weight | Outdoor | kg 25 | 25 | 50 | 60 |
| Power Supply Cable | (Includes earth) | No *mm ² 3 x 0.75 | 3 x 0.75 | 3 x 0.75 | 3 x 0.75 |
| Blower Motor | Input / Output | W 27.6 / 7.8 | 34.3 / 15.1 | 50 / 19 | 58 / 25.6 |
| Max Piping | Elevation / Length | M 7 / 15 | 7 / 15 | 15 / 30 | 15 / 30 |
| Drain Hose | | mm 26.5 | 26.5 | 26.5 | 26.5 |
| Running Current | Cooling / Heating | A 4.2 / 4.0 | 6.0 / 4.8 | 9.2 / 8.4 | 12.6 / 12.6 |
| Air Circulation | | CMM / CFM 23 (812) | 23 (812) | 42 (1,483) | 42 (1,483) |

LG Electronics South Africa (Pty) Ltd
 Rand Airport Road, Raceway Industrial Park, Monte Carlo Drive,
 Gosforth Park, Germiston, 1459
 P.O. Box 973, Alberton, South Africa, 1430
 Telephone number: 011 323 8000
 Website address: www.lgeaircon.com

Other Contacts

Johannesburg Toll Free: 0800 54 54 54
 Cape Town: 021 551 3284
 Durban: 031 716 5454



HS-H0964GA0



HS-H1264GA0



HS-H1865GA0



HS-H2665GA0